



Triangle shape nozzles with combined thrust (rear jets) and breaking through (4 front jets) actions.

	1/4" F	1/2" F	3/4" F	1" F	1 1/4" F	
Ø x L (mm)	20x35	30x59	50x92	59x105	75x135	
Weight (lb)	1.5 oz	0.5	1.5	2.25	4.25	
Front jets	0° / 15°	0° / 15° (M4)	0° / 20° (M6)	0° / 20° (M6*)	0° / 20° (M6)	
Rear jets	25°	20° (M4)	20° (M4)	20° (M6*)	20° (M10)	
Inserts	Drilled	M4	M6	M6 TE	M6/M10	
Pressure (psi)	2,000-4,000	2,000-4,000	2,000-4,000	2,000-3,000	2,000-3,000	
Flow rate (gpm)	6-8	10-25	25-50	50-80	50-120	
Part numbers	5550.05	5550.10	5550.20			
w/ceramic inserts			5550.20C	5550.30C	5550.40C	

(*) the version is fitted with hexagonal external head ceramic inserts.

Applications

- Breaking through obstructions (grease, roots, blockage, ice);
- Unblocking clogged pipes;
- Flow direction cleaning (i.e. from house to sewer)



5550.30C Raut 1" with ceramic inserts